



Adhesive/Binder

PU-825 Water based polyurethane flocking adhesive

DESCRIPTION	Water based polyurethane electrostatic flocking adhesive is designed for rubber, PVC, PU, shoes materials etc. It is VOC free and formaldehyde free	
TYPE	Water based polyurethane dispersion (PE/PU)	
KEY FEATURES	 VOC and formaldehyde-free Stable, good water resistance Non-toxic, non-irritating, easy to clean Excellent dry and wet wipe resistance performance Excellent adhesion, can heat resistant at 90 °C after add curing agent 	
	Appearance	White and bluish liquid
	pH	7.0-8.0
TYPICAL	Solid content	40±1%
	Charge	Anionic
PROPERTIES	Viscosity (25°C)	100-500cP
	Softening point	50-55℃
	Density	1.05 ± 0.2
NOTICE	 Recommend: If want improve the performance, add 5% curing agent, then stir uniformly Application way: Spray, roller, brush screen printing etc. Open time within 4 minutes, if more than this time, may reduce the flocking fastness Don't mix with other different properties of adhesives 	
APPLICATION	 Electrostatic flocking adhesive for rubber, PVC, PU, shoes materials etc. 	
STORAGE AND HANDLING	 Available in 200 kg/ barrel or 25 kg/ barrel Store products in tightly closed original containers at 6-35°C, avoid low and high temperature Shelf life: 6-9 months from delivery date According to non-dangerous goods transport 	