



## **Architectural Coatings**

## **SA-212 Styrene Acrylic Emulsion for Real Stone Paint**

DESCRIPTION	Special styrene acrylic emulsion developed by imported special additives and functional monomers. It has good film-forming performance strong adhesive force. It can solve the problem of stone-like coating water blushing.	
ТҮРЕ	Styrene acrylic copolymer dispersion	
KEY FEATURES	<ul> <li>Fast dry</li> <li>Good film-forming performance</li> <li>Excellent adhesion and excellent yellowing resistance</li> <li>Good water and blush resistance, high hardness, tough film and vivid stone feeling</li> <li>High cost-performance and widely used in medium and top</li> </ul>	
	grade stone coatings	used in medium and top
TYPICAL PROPERTIES	Appearance pH Solid content Glass Transition Temperature Viscosity (25°C) Ca <sup>2+</sup> stability 5%CaCl <sub>2</sub> : emulsion =1:3, 48h, No Flocculation, No Stratification.	Milky white liquid 7-9 46±1% 30°C 1800-4500cP Pass
APPLICATION	Real stone paint/coatings	
STORAGE AND HANDLING	<ul> <li>Available in 200 kg/ barrel or 25 kg/ barrel</li> <li>Store products in tightly closed original containers at 5-40°C</li> <li>Shelf life: 9 months from delivery date</li> <li>According to non-dangerous goods transport</li> </ul>	

Anhui Sinograce Chemical Co., Ltd. Tel: +86-0551-63459511

Email: sales@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 15855525589