



Wood Coating / Paint

PU-105 Water based polyurethane for wood topcoat

DESCRIPTION

Water based polyurethane is an easy-to-apply, quick clean-up, crystal clear finish for interior wood surfaces. Formulated with state-of-the-art resins, this clear finish is non-yellowing and perfect for use over light or natural wood colors. It dries quickly and can be recoated in only two hours. This extremely durable finish resists abrasion, alcohol, water and virtually all household chemicals. This product has superior hardness and adhesion.

TYPE	Aromatic polyurethane dispersion	
KEY FEATURES	 Fast drying and easy-to-apply Superior durability against nicks, scratches, spills and stains For interior and protected exterior wood surfaces, doors, furniture, cabinets Use on bare, stained or previously varnished or finished wood 	
	105A: Clear Gloss	105B: Clear Satin
TYPICAL PROPERTIES	105C: Clear Semi-Gloss	105D: Matte
	Appearance	Translucent liquid
	pH	7-8
	Solid content	40±1%
	Charge	Anionic
	Viscosity (25℃)	300-600cP
	Pencil hardness	≥1H
	Dry time for Touch (25℃)	1-2 hours
	Dry time for Foot Traffic (25℃)	24 hours
APPLICATION	Interior bare and stained wood surfaces and furniture	
STORAGE	• Available in 200 kg/ barrel or 25 kg/ barrel	
AND	 Store products in tightly closed original containers at 5-40°C Shelf life: 9 months from delivery date 	
HANDLING	 According to non-dangerous goods transport 	

Anhui Sinograce Chemical Co., Ltd. Tel: +86-0551-63459511

Email: mia@sinogracechem.com

Add.: Hefei city, Anhui province, China

Mob: +86 17756043696