METAL SURFACE TEATMENT



Modified non-phosphate degreaser for sheet and alloy

MC-FM7230

	1110 1111.200
FEATURE	 Non-phosphate and no heavy metal ion Two-component liquid degreaser and alkali degreaser used with surfactant Can effectively remove cold rolled steel, cast iron and precision parts surface grease, rust, dust and dirt.
APPLICATION	 Appearance: Colorless or yellowish liquid Applied temperature: Normal temperature~45°C MC-DE6280B applied concentration: 4~6% Treatment time: 3~8min Treatment way: Dip or spray Add the MC-FM7230 40~60kg into a tank and add the water to 1000L. Then using treat the metal by dipping or spraying.
ATTRIXATION)	
PROCESS	Please remove rust, dust oil and other pollution by overflow or other way in time. It need to supplement the MC-FM7230, when the effect can not meet your request.
	Free alkalinity test method: Firstly, add 10ml aqueous into an Erlenmeyer flask. Then add 0.1~0.5ml phenolphthalein indicator. Using 0.1mol/L HCl standard solution to titrate it. While the solution changes from red to colorless. The consumption volume of 0.1mol/L HCl standard solution is the free alkalinity value.
APPLICATION	Cold rolled steel, cast ironAlloy etc.
NOTE	 Please wear the protective gloves when using it. MC-FM7230 is acid liquid and wear the protective equipment while using it. It contains the phosphate and please treat the waste liquid before discharge. Wash immediately with water when skin encounter the cleaning agent.
STORAGE AND	 Available in 200 kg/ barrel or 25 kg/ barrel Storage period: ~12 months in closed containers, shady and

Anhui Sinograce Chemical Co., Ltd. Add.: Hefei city, Anhui province, China Tel: +86-0551-63459511 Mob: +86 15855525589

dry place

Email: sales@sinogracechem.com

HANDLING